








RoHS  
Compliant  
2011/65/EU


## DIMENSIONS




P.C.B MOUNTING PATTERN DIMENSION  
The following soldering patterns are recommended for reflow soldering



## CIRCUIT DIAGRAM



## PRODUCT IMAGE



## ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA
Contact Resistance	100mΩ Max.
Travel	0.2 ± 0.1mm
Operating Force	200±50gf
Operating Life(cycles)	50,000

REV	REVISION RECORD	DATE	SCALE: 1:1	TOLERANCES	DR	KEN	PART NO.:
A0	NEW		SCALE: 1:1	LINEAR	CHKD	FRDS	TS-1851SN
			UNITS:mm	.X ±0.20			
			SIZE:A4	.XX ±0.10	APPD	ANGEL	TITLE:
			SHEET:1/1	.XXX ±0.03	WEB	WWW.HUATN.COM	TACT SWITCH

# HUATN

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HUATN ELECTRONICS CO.,LTD.AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HUATN ELECTRONICS CO.,LTD.